KOWOSGAN X50

KOWOSCAN X50

X-ray HiRes Film Digitizer according to DIN EN ISO 14096






Digitization of X-ray films within seconds meeting digitization quality class DS (ISO 14096)

KOWOSCAN X50 NDT Film Digitizer

The KOWOSCAN X50 is a very effective and fast tool for digitizing X-ray films in digitization quality class DS using completely new technique. An Ultra HighRes 2D digital camera takes images of X-ray films which are placed on a highly uniform illuminated screen within seconds. Several smaller films can be placed on the large scanning area for simultaneous scanning. The easy to use KowoScan software recognizes the film size and separates multiple films to single images automatically to store in DICONDE or TIF format. A sophisticated filter function enables to find smallest details in the images for instant evaluation and an automated Test Report function provides verification of most important parameters of the system.

Features and advantages:

- ♦ very high throughput for fast digitization of high amount of films
- ♦ several smaller films within one scan, automatic film size recognition
- ♦ very low maintenance efforts, no movable parts
- ♦ Region Of Interest (ROI) function for perfect film region
- ♦ measurement of optical density with the "mouse pointer"
- ♦ magnification and window leveling with the mouse
- ♦ magnification, mirroring, rotating, display 1:1 and full screen function
- ♦ automatic calibration in density and geometry (with test chart)
- ♦ DICONDE tag editor with automatic functions
- ♦ easy linking to any evaluation software



Specification:

Scanning size: 300 x 450 mm - max. length: 480 mm (with max. width of 10 cm) Digitization quality class: DS *) according to DIN EN ISO 14096 and ASTM E1936 Scanner pixel sizes: class DS: 30 μ m, 60 μ m, 100 μ m; class DB: 50 μ m, 70 μ m, 85 μ m Scanning resolution (vSRb): 40 μ m (with Duplex wire type IQI using 30 μ m pixel size) class DS 30 μ m: 45 s; 60 μ m: 24 s; fast scan (no class): 8 s Density range (DWR): D 0.2 ... D 5.0 with linearity of D 0.02 (all classes) D 0.2 ... D 4.5 with $\Delta D_{CS} < 0.02$ (class DS)

Data format: DICONDE or TIFF (16 Bit density or gray value images)

Scanner resolution (30 μ m): 14870 x 9920 pixel (full area); 22 Bit image sampling (eff.)

Scanner resolution (60 μ m): 7435 x 4960 pixel (full area); 22 Bit image sampling (eff.)

Communication port: USB 3.0

Power Supply: 100 ... 240 V, 50 ... 60 Hz / 24 V DC, 120 W

Dimensions: 57 x 44 x 79 cm (W x D x H)


Weight unit: 29.8 kg plus 1.0 kg (external power supply)

*) class DS cannot be reached for films exposed lower 100 kV due to 30µm min. pixel size



Scope of supply:

KOWOSCAN X50 Film Digitizer	Art. No.: 13 42100
complete with Test certificate, Certificate of Conformity	
KowoScan Software	Art. No.: 13 42107
KOWOSCAN Resolution Test Chart	Art. No.: 13 42110
KOWOSCAN Density Step Tablet	Art. No.: 13 42115
Mask for films - 14x17 inch (1-fold)	Art. No.: 13 42161






Accessories:

Reference Radiograph, ASTM E1936 (EPRI) Art. No.: 11 00340
Mask for Reference Radiograph, ASTM E1936 Art. No.: 13 42125

Mask for films	Art. No.:	Mask for films	Art. No.:	Mask for films	Art. No.:
10x12 cm (8-fold)	13 42131	6x16 cm (6-fold)	13 42142	8x18 cm (4-fold)	13 42151
10x16 cm (4-fold)	<i>13 42132</i>	6x24 cm (6-fold)	13 42143	8x36 cm (3-fold)	13 42152
10x24 cm (4-fold)	<i>13 42133</i>	6x32 cm (4-fold)	13 42144	13x18 cm (4-fold)	13 42154
10x40 cm (2-fold)	13 42134	6x40 cm (4-fold)	13 42145	15x40 cm (1-fold)	13 42155
10x48 cm (1-fold)	<i>13 42135</i>	6x48 cm (1-fold)	13 42146	18x24 cm (2-fold)	13 42156
10x20 cm (4-fold)	<i>13 42136</i>	6x30 cm (4-fold)	13 42147	24x30 cm (1-fold)	13 42157
10x30 cm (2-fold)	<i>13 42137</i>	6x36 cm (4-fold)	13 42148	30x40 cm (1-fold)	13 42158
6x12 cm (8-fold)	13 42141	6x16 cm (8-fold)	13 42149	14x17 in (1-fold)	13 42161





联系人: 曾祥满 手机: 13632925349 QQ: 812401203 电话: 0755-28896837

地址:深圳市龙岗区沙平北路111号6008 网址: www.zykang.cn 邮箱: zykang2021@163.com